

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C11D 3/42, 17/04, 3/40	A1	(11) International Publication Number: WO 00/36074 (43) International Publication Date: 22 June 2000 (22.06.00)
(21) International Application Number: PCT/EP99/09374 (22) International Filing Date: 30 November 1999 (30.11.99) (30) Priority Data: 09/213,045 16 December 1998 (16.12.98) US (71) Applicant (for all designated States except AU BB CA CY GB GD GH IE IL IN KE LK LS MN MW NZ SD SG SZ TT UG ZA): UNILEVER N.V. [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL). (71) Applicant (for AU BB CA CR CY DM GB GD GH IE IL KE LK LS MA MN MW NZ SD SG SZ TT TZ UG ZA only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London, Greater London EC4P 4BQ (GB). (71) Applicant (for IN only): HINDUSTAN LEVER LTD [IN/IN]; Hindustan Lever House, 165-166 Backbay Reclamation, 400 020 Mumbai (IN).		(72) Inventors: MURPHY, Dennis, Stephen; Lever Brothers Development, 45 River Road, Edgewater, NJ 07020 (US). NEUSER, Kristina, Marie; Lever Brothers Development, 45 River Road, Edgewater, NJ 07020 (US). BAE-LEE, Myongsuk; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). HSU, Feng-Lung, Gordon; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). KUZMENKA, Daniel, Joseph; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). BORY, Barbara, Helen; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). (74) Agent: KAN, Jacob, Hendrik; Unilever NV, Patent Department, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL). (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: TRANSPARENT/TRANSLUCENT LIQUID COMPOSITIONS IN CLEAR BOTTLES COMPRISING COLORANT AND FLUORESCENT DYE OR UV ABSORBER (57) Abstract A translucent or transparent aqueous heavy duty liquid in a clear bottle comprising colorant dye and fluorescent dye and/or UV absorber to protect said colorant dye.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

TRANSPARENT/TRANSLUCENT LIQUID COMPOSITIONS
IN CLEAR BOTTLES COMPRISING COLORANT AND
FLUORESCENT DYE OR UV ABSORBER

FIELD OF THE INVENTION

5 The present invention relates to aqueous, transparent or translucent heavy duty liquid laundry detergents in clear bottles comprising both colorants and fluorescent dyes (f-dyes) and/or UV absorbers. The f-dyes and/or UV absorbers protect the colorants present in the HDL composition from damage by harmful UV radiation. The present invention also relates to a method of
10 reducing destruction of colorant dye in a transparent or translucent liquid composition in a clear bottle.

BACKGROUND OF THE INVENTION

Liquid detergents have traditionally been sold in opaque bottles. However, use of clear (for the present purpose used synonymiously with the terms transparent
15 and translucent) bottles can be aesthetically appealing to consumers as they can see the color of the product, its consistency, and suspended particles if they are present. However, the use of clear bottles can lead to destruction of colorant by UV light. By UV light is meant light having wavelength of about 250 to about 460 nanometers (nm). Specifically, UVA generally is in range 320-400
20 nm, UVB about 290 to 320 nm and UVC below 290 nm, down to about 250 nm.

It has been known in the art that UV absorbers can be added to the bottle material during manufacture of clear bottles to protect them from becoming brittle and to protect the ingredients inside the bottle. For instance, in GB
25 2228940 the use of a dicarboxylate in polyester bottles to protect contents - mainly food - from 320-360 nm is described.

In EU 0461537A2 the use of film formers for blocking UV radiation from passing through glass bottles is described. While use of such ingredients can block the transmission of UV light through clear bottles, UV absorbers for inclusion in bottle material are expensive, and must be added when bottle material is hot and molten and there is the risk of burning the operator.

WO 97/26315 (Colgate discloses transparent containers with specific chromacity defined by x and y values. Specific dyes in the liquid are used to match the container. The reference does not disclose combination of colorant dye and UV absorber or beneficial effect

GB 1,303,810 discloses clear liquid medium and visually defined particles suspended therein. Detergent compositions with colorant dye and UV absorber are not disclosed.

U.S. Patent No. 3,812,042 to Verdier discloses clear package containing liquids with a viscosity and clarity control system comprising urea, lower aliphatic alcohol and optional hydrotrope.

20 BRIEF DESCRIPTION OF THE INVENTION

It has now surprisingly been found that a relatively small amount of f-dye or UV absorber, when added to a liquid containing colorant dye, has the ability to dramatically reduce the destruction of colorant dye by UV light. This is unexpected in that the level of additive is small (0.001 to about 3%) and is dispersed throughout the liquid matrix. The use of f-dye has the advantage that is an ingredient already frequently used in HDL's and thus adds little or no additional cost, and it can be added at lower temperatures for safety than found with molten bottle materials. UV absorber added to the HDL has the advantage that it can be added at lower and safer temperatures than adding UV absorber to molten bottle material.

Accordingly, the present invention relates to a transparent or translucent aqueous heavy duty liquid composition in a clear bottle comprising:

- 5 (a) 10 to 85% by wt. of a surfactant selected from the group consisting of anionic, nonionic, cationic, amphoteric, zwitterionic surfactants and mixtures thereof;
- (b) 0.001 to 1% by wt. of a colorant dye; and
- (c) 0.001 to 3% by wt. of a fluorescent dye and/or 0.001 to 3% by wt of a UV absorber;
- 10 wherein the composition has about 50% light transmittance or greater using 1 cm cuvette at wavelength of 410-800 nanometers; and
- wherein the bottle has a light transmittance of greater than 25% at wavelength of about 410-800 nm.

15

DETAILED DESCRIPTION OF THE INVENTION

The invention relates to enzyme containing transparent/translucent liquid duty liquids in clear bottles comprising relatively small amounts of f-dye or UV absorber to protect against destruction of colorant dye (e.g., caused by the light hitting dye molecules through the clear bottle).

20

UV Absorbers

Among preferred families of UV absorbers which may be used are benzophenones, salicyclates, benzotriazoles, hindered amines and alkoxy (e.g., methoxy) cinnamates. Recitation of these classes is not meant to be a limitation on other classes of UV absorbers which may be used.

25

Water soluble UV absorbers particularly useful for this application include, but are not limited to: phenyl benzimidazole sulfonic acid (sold as Neo Heliopan, Type Hydro by Haarmann and Reimer Corp.), 2-hydroxy-4-methoxybenzophenone-5-sulfonic acid (sold as Syntase 230 by Rhone-Poulenc

30

and Uvinul MS-40 by BASF Corp.), sodium 2,2'-dihydroxy-4,4'-dimethoxy-5-sulfobenzophenone (sold as Uvinul DS-49 by BASF Corp.), and PEG-25 paraaminobenzoic acid (sold as Uvinul P-25 by Basf Corp.).

- 5 Other UV absorbers which may be used are defined in McCutcheon's Volume 2, Functional Materials, North American Edition, published by the Manufacturing Confectioner Publishing Company (1997), a copy of which is hereby incorporated by reference into the subject application.
- 10 UV absorber may be present in the formulation with or without F-dye. UV absorber is used in the formulation from about 0.001% to about 3%, preferably from 0.001 to 1%, more preferably between 0.05% and 1%.

Fluorescent Dyes

- 15 Preferred classes of fluorescent dyes which may be used include stilbenes; coumarin and carbostyryl compounds; 1,3-diphenyl-2-pyrazolines; naphthalimides; benzazdyl substitution products of ethylene, phenylethylene, stilbene, thiophene; and combined heteroaromatics.
- 20 Among fluorescent dyes which may be used are also the sulfonic acid salts of diamino stilbene derivatives such as taught in U.S. Patent No. 2,784,220 to Spiegler or U.S. Patent No. 2,612,510 to Wilson et al., both of which are hereby incorporated by reference. Polymeric fluorescent whitening agent as taught in U.S. Patent No. 5,082,578, hereby incorporated by reference into the subject
- 25 application, are also contemplated by this invention.

Finally, other dyes which may be used are defined in McCutcheon's Volume 2, Functional Materials, North American Edition as noted above in connection with UV absorbers.

Fluorescent dyes particularly useful for this application include, but are not limited to: the distyrylbiphenyl types such as Tinopal CBS-X from Ciba Geigy Corp. and the cyanuric chloride/diaminostilbene types such as Tinopal AMS, DMS, 5BM, and UNPA from Ciba Geigy Corp. and Blankophor DML from Mobay. Fluorescent dye may be present in the formulation with or without UV absorbing. F-dye is used in the formulation from about 0.001% to about 3%, preferably from 0.001 to 1%, more preferably between 0.05% and 0.5%.

Colorant Dyes

Any type of colorant dye which may be destroyed by UV light is considered as part of the invention. Non limiting examples of such include, but are not limited to the following: Hidacid blue from Hilton Davis; Acid blue 145 from Crompton Knowles and Tri-Con; Pigment Green No. 7, FD&C Green No. 7, Acid Blue 80, Acid Violet 48, and Acid Yellow 17 from Sandoz Corp.; D&C Yellow No. 10 from Warner Jenkinson Corp.

The dyes are present in an amount of from 0.001% to 1%, preferably 0.01 to 0.4% of the composition.

20

Detergent Compositions

Detergent Active

The compositions of the invention contains one or more surface active agents (surfactants) selected from the group consisting of anionic, nonionic, cationic, ampholytic and zwitterionic surfactants or mixtures thereof. The preferred surfactant detergents for use in the present invention are mixtures of anionic and nonionic surfactants although it is to be understood that any surfactant may be used alone or in combination with any other surfactant or surfactants. The surfactant should comprise at least 10% by wt. of the composition, e.g., 11% to

75%, preferably at least 15% to 70% of the total composition, more preferably 16% to 65%, even more preferably 20% to 65%.

Nonionic Surfactant

- 5 Nonionic synthetic organic detergents which can be used with the invention, alone or in combination with other surfactants, are described below.

As is well known, the nonionic detergents are characterized by the presence of an organic hydrophobic group and an organic hydrophilic group and are
10 typically produced by the condensation of an organic aliphatic or alkyl aromatic hydrophobic compound with ethylene oxide (hydrophilic in nature). Typical suitable nonionic surfactants are those disclosed in U.S. Pat. Nos. 4,316,812 and 3,630,929.

- 15 Usually, the nonionic detergents are polyalkoxylated lipophiles wherein the desired hydrophile-lipophile balance is obtained from addition of a hydrophilic poly-lower alkoxy group to a lipophilic moiety. A preferred class of nonionic detergent is the alkoxylated alkanols wherein the alkanol is of 9 to 18 carbon atoms and wherein the number of moles of alkylene oxide (of 2 or 3 carbon
20 atoms) is from 3 to 12. Of such materials it is preferred to employ those wherein the alkanol is a fatty alcohol of 9 to 11 or 12 to 15 carbon atoms and which contain from 5 to 8 or 5 to 9 alkoxy groups per mole.

Exemplary of such compounds are those wherein the alkanol is of 12 to 15
25 carbon atoms and which contain about 7 ethylene oxide groups per mole, e.g. Neodol 25-7 and Neodol 23-6.5, which products are made by Shell Chemical Company, Inc. The former is a condensation product of a mixture of higher fatty alcohols averaging about 12 to 15 carbon atoms, with about 7 moles of ethylene oxide and the latter is a corresponding mixture wherein the carbon atoms
30 content of the higher fatty alcohol is 12 to 13 and the number of ethylene oxide

groups present averages about 6.5. The higher alcohols are primary alkanols.

Other useful nonionics are represented by the commercially well-known class of nonionics sold under the trademark Plurafac. The Plurafacs are the reaction products of a higher linear alcohol and a mixture of ethylene and propylene oxides, containing a mixed chain of ethylene oxide and propylene oxide, terminated by a hydroxyl group. Examples include C₁₃-C₁₅ fatty alcohol condensed with 6 moles ethylene oxide and 3 moles propylene oxide, C₁₃-C₁₅ fatty alcohol condensed with 7 moles propylene oxide and 4 moles ethylene oxide, C₁₃-C₁₅ fatty alcohol condensed with 5 moles propylene oxide and 10 moles ethylene oxide, or mixtures of any of the above.

Another group of liquid nonionics are commercially available from Shell Chemical Company, Inc. under the Dobanol trademark: Dobanol 91-5 is an ethoxylated C₉-C₁₁ fatty alcohol with an average of 5 moles ethylene oxide and Dobanol 23-7 is an ethoxylated C₁₂-C₁₅ fatty alcohol with an average of 7 moles ethylene oxide per mole of fatty alcohol.

In the compositions of this invention, preferred nonionic surfactants include the C₁₂-C₁₅ primary fatty alcohols with relatively narrow contents of ethylene oxide in the range of from about 7 to 9 moles, and the C₉ to C₁₁ fatty alcohols ethoxylated with about 5-6 moles ethylene oxide.

Another class of nonionic surfactants which can be used in accordance with this invention are glycoside surfactants. Glycoside surfactants suitable for use in accordance with the present invention include those of the formula:



wherein R is a monovalent organic radical containing from about 6 to about 30 (preferably from about 8 to about 18) carbon atoms; R' is a divalent

hydrocarbon radical containing from about 2 to 4 carbons atoms; O is an oxygen atom; y is a number which can have an average value of from 0 to about 12 but which is most preferably zero; Z is a moiety derived from a reducing saccharide containing 5 or 6 carbon atoms; and x is a number having
5 an average value of from 1 to about 10 (preferably from about 1.5 to about 10).

A particularly preferred group of glycoside surfactants for use in the practice of this invention includes those of the formula above in which R is a monovalent organic radical (linear or branched) containing from about 6 to about
10 18 (especially from about 8 to about 18) carbon atoms; y is zero; z is glucose or a moiety derived therefrom; x is a number having an average value of from 1 to about 4 (preferably from about 1 to 4).

Nonionic surfactants particularly useful for this application include, but are not
15 limited to: alcohol ethoxylates (e.g. Neodol 25-9 from Shell Chemical Co.), alkyl phenol ethoxylates (e.g. Tergitol NP-9 from Union Carbide Corp.), alkylpolyglucosides (e.g. Glucapon 600CS from Henkel Corp.), polyoxyethylenated polyoxypropylene glycols (e.g. Pluronic L-65 from BASF Corp.), sorbitol esters (e.g. Emsorb 2515 from Henkel Corp.) ,
20 polyoxyethylenated sorbitol esters (e.g. Emsorb 6900 from Henkel Corp.), alkanolamides (e.g. Alkamide DC212/SE from Rhone-Poulenc Co.), and N-alkylpyrrolidones (e.g. Surfadone LP-100 from ISP Technologies Inc.).

Nonionic surfactant is used in the formulation from about 0% to about 70%,
25 preferably between 5% and 50%, more preferably 10-40% by weight.

Mixtures of two or more of the nonionic surfactants can be used.

Anionic Surfactant Detergents

Anionic surface active agents which may be used in the present invention are those surface active compounds which contain a long chain hydrocarbon
5 hydrophobic group in their molecular structure and a hydrophilic group, i.e.; water solubilizing group such as sulfonate or sulfate group. The anionic surface active agents include the alkali metal (e.g. sodium and potassium) water soluble higher alkyl benzene sulfonates, alkyl sulfonates, alkyl sulfates and the alkyl polyether sulfates. They may also include fatty acid or fatty acid soaps. The
10 preferred anionic surface active agents are the alkali metal, ammonium or alkanolamide salts of higher alkyl benzene sulfonates and alkali metal, ammonium or alkanolamide salts of higher alkyl sulfonates. Preferred higher alkyl sulfonates are those in which the alkyl groups contain 8 to 26 carbon atoms, preferably 12 to 22 carbon atoms and more preferably 14 to 18 carbon
15 atoms. The alkyl group in the alkyl benzene sulfonate preferably contains 8 to 16 carbon atoms and more preferably 10 to 15 carbon atoms. A particularly preferred alkyl benzene sulfonate is the sodium or potassium dodecyl benzene sulfonate, e.g. sodium linear dodecyl benzene sulfonate. The primary and secondary alkyl sulfonates can be made by reacting long chain alpha-olefins
20 with sulfites or bisulfites, e.g. sodium bisulfite. The alkyl sulfonates can also be made by reacting long chain normal paraffin hydrocarbons with sulfur dioxide and oxygen as described in U.S. Pat. Nos. 2,503,280, 2,507,088, 3,372,188 and 3,260,741 to obtain normal or secondary higher alkyl sulfonates suitable for use as surfactant detergents.

25

The alkyl substituent is preferably linear, i.e. normal alkyl, however, branched chain alkyl sulfonates can be employed, although they are not as good with respect to biodegradability. The alkane, i.e. alkyl, substituent may be terminally sulfonated or may be joined, for example, to the carbon atom of the chain, i.e.
30 may be a secondary sulfonate. It is understood in the art that the substituent

may be joined to any carbon on the alkyl chain. The higher alkyl sulfonates can be used as the alkali metal salts, such as sodium and potassium. The preferred salts are the sodium salts. The preferred alkyl sulfonates are the C10 to C18 primary normal alkyl sodium and potassium sulfonates, with the C10 to C15 primary normal alkyl sulfonate salt being more preferred.

Mixtures of higher alkyl benzene sulfonates and higher alkyl sulfonates can be used as well as mixtures of higher alkyl benzene sulfonates and higher alkyl polyether sulfates.

10


The alkali metal alkyl benzene sulfonate can be used in an amount of 0 to 70%, preferably 10 to 50% and more preferably 10 to 20% by weight.

The alkali metal sulfonate can be used in admixture with the alkylbenzene sulfonate in an amount of 0 to 70%, preferably 10 to 50% by weight.

Also normal alkyl and branched chain alkyl sulfates (e.g., primary alkyl sulfates) may be used as the anionic component).

20 The higher alkyl polyether sulfates used in accordance with the present invention can be normal or branched chain alkyl and contain lower alkoxy groups which can contain two or three carbon atoms. The normal higher alkyl polyether sulfates are preferred in that they have a higher degree of biodegradability than the branched chain alkyl and the lower poly alkoxy groups
25 are preferably ethoxy groups.

The preferred higher alkyl poly ethoxy sulfates used in accordance with the present invention are represented by the formula:




5

where R' is C₈ to C₂₀ alkyl, preferably C₁₀ to C₁₈ and more preferably C₁₂ to C₁₅; P is 2 to 8, preferably 2 to 6, and more preferably 2 to 4; and M is an alkali metal, such as sodium and potassium, or an ammonium cation. The sodium and potassium salts are preferred.

10

A preferred higher alkyl poly ethoxylated sulfate is the sodium salt of a triethoxy C₁₂ to C₁₅ alcohol sulfate having the formula:



15

Examples of suitable alkyl ethoxy sulfates that can be used in accordance with the present invention are C₁₂₋₁₅ normal or primary alkyl triethoxy sulfate, sodium salt; n-decyl diethoxy sulfate, sodium salt; C₁₂ primary alkyl diethoxy sulfate, ammonium salt; C₁₂ primary alkyl triethoxy sulfate, sodium salt; C₁₅ primary
20 alkyl tetraethoxy sulfate, sodium salt, mixed C₁₄₋₁₅ normal primary alkyl mixed tri- and tetraethoxy sulfate, sodium salt; stearyl pentaethoxy sulfate, sodium salt; and mixed C₁₀₋₁₈ normal primary alkyl triethoxy sulfate, potassium salt.

The normal alkyl ethoxy sulfates are readily biodegradable and are preferred.

25 The alkyl poly-lower alkoxy sulfates can be used in mixtures with each other and/or in mixtures with the above discussed higher alkyl benzene, alkyl sulfonates, or alkyl sulfates.

The alkali metal higher alkyl poly ethoxy sulfate can be used with the

30 alkylbenzene sulfonate and/or with an alkyl sulfonate or sulfonate, in an amount

of 0 to 70%, preferably 10 to 50% and more preferably 10 to 20% by weight of entire composition.

Anionic surfactants particularly useful for this application include, but are not limited to: linear alkyl benzene sulfonates (e.g. Vista C-500 from Vista Chemical Co.), alkyl sulfates (e.g. Polystep B-5 from Stepan Co.), polyoxyethylenated alkyl sulfates (e.g. Standapol ES-3 from Stepan Co.), alpha olefin sulfonates (e.g. Witconate AOS from Witco Corp.), alpha sulfo methyl esters (e.g. Alpha-Step MC-48 from Stepan Co.) and isethionates (e.g. Jordapon CI from PPG Industries Inc.).

Anionic surfactant is used in the formulation from about 0% to about 60%, preferably between 5% and 40%, more preferably 8 to 25% by weight.

15 **Cationic Surfactants**

Many cationic surfactants are known in the art, and almost any cationic surfactant having at least one long chain alkyl group of about 10 to 24 carbon atoms is suitable in the present invention. Such compounds are described in "Cationic Surfactants", Jungermann, 1970, incorporated by reference.

20

Specific cationic surfactants which can be used as surfactants in the subject invention are described in detail in U.S. Pat. No. 4,497,718, hereby incorporated by reference.

25 As with the nonionic and anionic surfactants, the compositions of the invention may use cationic surfactants alone or in combination with any of the other surfactants known in the art. Of course, the compositions may contain no cationic surfactants at all.

30 **Amphoteric Surfactants**

- Ampholytic synthetic detergents can be broadly described as derivatives of aliphatic or aliphatic derivatives of heterocyclic secondary and tertiary amines in which the aliphatic radical may be a straight chain or a branched and wherein one of the aliphatic substituents contains from about 8 to 18 carbon atoms and
- 5 at least one contains an anionic water-solubilizing group, e.g. carboxy, sulfonate, sulfate. Examples of compounds falling within this definition are sodium 3(dodecylamino)propionate, sodium 3-(dodecylamino)propane-1-sulfonate, sodium 2-(dodecylamino)ethyl sulfate, sodium 2-(dimethylamino)octadecanoate, disodium 3-(N-
- 10 carboxymethyldodecylamino)propane 1-sulfonate, disodium octadecyl-imminodiacetate, sodium 1-carboxymethyl-2-undecylimidazole, and sodium N,N-bis(2-hydroxyethyl)-2-sulfato-3-dodecoxypropylamine. Sodium 3-(dodecylamino)propane-1-sulfonate is preferred.
- 15 Zwitterionic surfactants can be broadly described as derivatives of secondary and tertiary amines, derivatives of heterocyclic secondary and tertiary amines, or derivatives of quaternary ammonium, quaternary phosphonium or tertiary sulfonium compounds. The cationic atom in the quaternary compound can be part of a heterocyclic ring. In all of these compounds there is at least one
- 20 aliphatic group, straight chain or branched, containing from about 3 to 18 carbon atoms and at least one aliphatic substituent containing an anionic water solubilizing group, e.g., carboxy, sulfonate, sulfate, phosphate, or phosphonate.

Specific examples of zwitterionic surfactants which may be used are set forth in

25 U.S. Pat. No. 4,062,647, hereby incorporated by reference.

The amount of amphoteric used may vary from 0 to 50% by weight, preferably 1 to 30% by weight.

It should be noted that the compositions of the invention are preferably

30 isotropic (by which is generally understood to be a homogenous phase when

viewed macroscopically) and either transparent or translucent.

Total surfactant used must be at least 10%, preferably at least 15%, more preferably at least 20% by wt.

5

Builders/Electrolyte

Builders which can be used according to this invention include conventional alkaline detergency builders, inorganic or organic, which can be used at levels from about 0% to about 50% by weight of the composition, preferably from 3%
10 to about 35% by weight.

As used herein, the term electrolyte means any water-soluble salt.

Preferably the composition comprises at least 1.0% by weight, more preferably
15 at least 5.0% by weight, most preferably at least 10.0% by weight of electrolyte. The electrolyte may also be a detergency builder, such as the inorganic builder sodium tripolyphosphate, or it may be a non-functional electrolyte such as sodium sulfate or chloride. Preferably the inorganic builder comprises all or part of the electrolyte.

20

The composition may comprise at least about 1%, preferably at least about 3%, preferably 3% to as much as about 50% by weight electrolyte.

The compositions of the invention are capable of suspending particulate solids,
25 although particularly preferred are those systems where such solids are actually in suspension. The solids may be undissolved electrolyte, the same as or different from the electrolyte in solution, the latter being saturated electrolyte. Additionally, or alternatively, they may be materials which are substantially insoluble in water alone. Examples of such substantially insoluble materials are
30 aluminosilicate builders and particles of calcite abrasive.

Examples of suitable inorganic alkaline detergency builders which may be used are water-soluble alkali metal phosphates, polyphosphates, borates, silicates and also carbonates. Specific examples of such salts are sodium and potassium triphosphates, pyrophosphates, orthophosphates, 5 hexametaphosphates, tetraborates, silicates, and carbonates.

Examples of suitable organic alkaline detergency builder salts are: (1) water-soluble amino polycarboxylates, e.g., sodium and potassium ethylenediaminetetraacetates, nitrilotriacetates and N-(2 hydroxyethyl)- 10 nitrilodiacetates; (2) water-soluble salts of phytic acid, e.g., sodium and potassium phytates (see U.S. Pat. No. 2,379,942); (3) water-soluble polyphosphonates, including specifically, sodium, potassium and lithium salts of ethane-1-hydroxy-1,1-diphosphonic acid; sodium, potassium and lithium salts of methylene diphosphonic acid; sodium, potassium and lithium salts of ethylene 15 diphosphonic acid; and sodium, potassium and lithium salts of ethane-1,1,2-triphosphonic acid. Other examples include the alkali metal salts of ethane-2-carboxy-1,1-diphosphonic acid hydroxymethanediphosphonic acid, carboxyldiphosphonic acid, ethane-1-hydroxy-1,1,2-triphosphonic acid, ethane-2-hydroxy-1,1,2-triphosphonic acid, propane-1,1,3,3-tetraphosphonic acid, 20 propane-1,1,2,3-tetraphosphonic acid, and propane-1,2,2,3-tetra-phosphonic acid; (4) water-soluble salts of polycarboxylates polymers and copolymers as described in U.S. Patent No. 3,308,067.

In addition, polycarboxylate builders can be used satisfactorily, including water- 25 soluble salts of mellitic acid, citric acid, and carboxymethyloxysuccinic acid, salts of polymers of itaconic acid and maleic acid, tartrate monosuccinate, tartrate disuccinate and mixtures thereof (TMS/TPS).

Certain zeolites or aluminosilicates can be used. One such aluminosilicate 30 which is useful in the compositions of the invention is an amorphous water-

insoluble hydrated compound of the formula $\text{Na}_x[(\text{AlO}_2)_y(\text{SiO}_2)]$, wherein x is a number from 1.0 to 1.2 and y is 1, said amorphous material being further characterized by a Mg^{++} exchange capacity of from about 50 mg eq. CaCO_3/g . and a particle diameter of from about 0.01 mm to about 5 mm. This ion
5 exchange builder is more fully described in British Pat. No. 1,470,250.

A second water-insoluble synthetic aluminosilicate ion exchange material useful herein is crystalline in nature and has the formula $\text{Na}_z[(\text{AlO}_2)_y(\text{SiO}_2)]_x\text{H}_2\text{O}$, wherein z and y are integers of at least 6; the molar ratio of z to y is in the range
10 from 1.0 to about 0.5, and x is an integer from about 15 to about 264; said aluminosilicate ion exchange material having a particle size diameter from about 0.1 mm to about 100 mm; a calcium ion exchange capacity on an anhydrous basis of at test about 200 milligrams equivalent of CaCO_3 hardness per gram; and a calcium exchange rate on an anhydrous basis of at least about
15 2 grains/gallon/minute/gram. These synthetic aluminosilicates are more fully described in British Patent No. 1,429,143.

Enzymes

Enzymes which may be used in this invention are described in greater detail
20 below.

If a lipase is used, the lipolytic enzyme may be either a fungal lipase producible by Humicola lanuginosa and Thermomyces lanuginosus, or a bacterial lipase which show a positive immunological cross-reaction with the antibody of the
25 lipase produced by the microorganism *Chromobacter viscosum* var. *lipolyticum* NRRL B-3673. This microorganism has been described in Dutch patent specification 154,269 of Toyo Jozo Kabushiki Kaisha and has been deposited with the Fermentation Research Institute, Agency of Industrial Science and Technology, Ministry of International Trade and Industry, Tokyo, Japan, and
30 added to the permanent collection under nr. KO Hatsu Ken Kin Ki 137 and is

available to the public at the United States Department of Agriculture, Agricultural Research Service, Northern Utilization and Development Division at Peoria, Ill., USA, under the nr. NRRL B-3673. The lipase produced by this microorganism is commercially available from Toyo Jozo Co., Tagata, Japan, 5 hereafter referred to as "TJ lipase". These bacterial lipases should show a positive immunological cross-reaction with the TJ lipase antibody, using the standard and well-known immune diffusion procedure according to Ouchterlony (Acta. Med. Scan., 133 pages 76-79 (1930)).

10 The preparation of the antiserum is carried out as follows:

Equal volumes of 0.1 mg/ml antigen and of Freund's adjuvant (complete or incomplete) are mixed until an emulsion is obtained. Two female rabbits are injected 45 with 2 ml samples of the emulsion according to the following

15 scheme:

- day 0: antigen in complete Freund's adjuvant
- day 4: antigen in complete Freund's adjuvant
- day 32: antigen in incomplete Freund's adjuvant
- day 64: booster of antigen in incomplete Freund's adjuvant

20

The serum containing the required antibody is prepared by centrifugation of clotted blood, taken on day 67.

The titre of the anti-TJ-lipase antiserum is determined by the inspection of 25 precipitation of serial dilutions of antigen and antiserum according to the Ouchterlony procedure. A dilution of antiserum was the dilution that still gave a visible precipitation with an antigen concentration of 0.1 mg/ml.

All bacterial lipases showing a positive immunological cross reaction with the 30 TJ-lipase antibody as hereabove described are lipases suitable in this

embodiment of the invention. Typical examples thereof are the lipase ex *Pseudomonas fluorescens* IAM 1057 (available from Amano Pharmaceutical Co., Nagoya, Japan, under the trade-name Amano-P lipase), the lipase ex *Pseudomonas fragi* FERM P 1339 (available under the trade-name Amano B),
5 the lipase ex *Pseudomonas nitroreducens* var. *lipolyticum* FERM P1338, the lipase ex *Pseudomonas* sp. (available under the trade-name Amano CES), the lipase ex *Pseudomonas cepacia*, lipases ex *Chromobacter viscosum*, e.g. *Chromobacter viscosum* var. *lipolyticum* NRRL B-3673, commercially available from Toyo Jozo Co., Tagata, Japan; and further *Chromobacter viscosum*
10 lipases from U.S. Biochemical Corp. USA and Diosynth Co., The Netherlands, and lipases ex *Pseudomonas gladioli*.

An example of a fungal lipase as defined above is the lipase ex *Humicola lanuginosa* available from Amano under the tradename Amano CE; the lipase
15 ex *Humicola lanuginosa* as described in the aforesaid European Patent Application 0,258,068 (NOVO), as well as the lipase obtained by cloning the gene from *Humicola lanuginosa* and expressing this gene in *Aspergillus oryzae*, commercially available from NOVO industri A/S under the tradename "Lipolase". This lipolase is a preferred lipase for use in the present invention.

20

While various specific lipase enzymes have been described above, it is to be understood that any lipase which can confer the desired lipolytic activity to the composition may be used and the invention is not intended to be limited in any way by specific choice of lipase enzyme.

25

The lipases of this embodiment of the invention are included in the liquid detergent composition in such an amount that the final composition has a lipolytic enzyme activity of from 100 to 0.005 LU/ml in the wash cycle, preferably 25 to 0.05 LU/ml when the formulation is dosed at a level of about 0.1-10, more
30 preferably 0.5-7, most preferably 1-2 g/liter.

A Lipase Unit (LU) is that amount of lipase which produces 1/mmol of titratable fatty acid per minute in a pH state under the following conditions: temperature 30°C.; pH =9.0; substrate is an emulsion of 3.3 wt. % of olive oil and 3,3% gum arabic, in the presence of 13 mmol/l Ca^{2+} and 20 mmol/l NaCl in 5 mmol/l Trisbuffer.

Naturally, mixtures of the above lipases can be used. The lipases can be used in their non-purified form or in a purified form, e.g. purified with the aid of well-known absorption methods, such as phenyl sepharose absorption techniques.

If a protease is used, the proteolytic enzyme can be of vegetable, animal or microorganism origin. Preferably, it is of the latter origin, which includes yeasts, fungi, molds and bacteria. Particularly preferred are bacterial subtilisin type proteases, obtained from e.g. particular strains of *B. subtilis* and *B. licheniformis*.

Examples of suitable commercially available proteases are Alcalase, Savinase, Esperase, all of NOVO Industri A/S; Maxatase and Maxacal of Gist-Brocades; Kazusase of Showa Denko; BPN and BPN' proteases and so on. The amount of proteolytic enzyme, included in the composition, ranges from 0.05-50,000 GU/mg. preferably 0.1 to 50 GU/mg, based on the final composition. Naturally, mixtures of different proteolytic enzymes may be used.

While various specific enzymes have been described above, it is to be understood that any protease which can confer the desired proteolytic activity to the composition may be used and this embodiment of the invention is not limited in any way by specific choice of proteolytic enzyme.

In addition to lipases or proteases, it is to be understood that other enzymes such as cellulases, oxidases, amylases, peroxidases and the like which are well known in the art may also be used with the composition of the invention. The enzymes may be used together with cofactors required to promote enzyme

activity, i.e., they may be used in enzyme systems, if required. It should also be understood that enzymes having mutations at various positions (e.g., enzymes engineered for performance and/or stability enhancement) are also contemplated by the invention. One example of an engineered commercially
5 available enzyme is Durazym from Novo.

Optional Ingredients

In addition to the enzymes mentioned above, a number of other optional ingredients may be used.

10

Alkalinity buffers which may be added to the compositions of the invention include monoethanolamine, triethanolamine, borax, sodium silicate and the like.

Hydrotropes which may be added to the invention include ethanol, sodium
15 xylene sulfonate, sodium cumene sulfonate and the like.

Other materials such as clays, particularly of the water-insoluble types, may be useful adjuncts in compositions of this invention. Particularly useful is bentonite. This material is primarily montmorillonite which is a hydrated aluminum silicate
20 in which about 1/6th of the aluminum atoms may be replaced by magnesium atoms and with which varying amounts of hydrogen, sodium, potassium, calcium, etc. may be loosely combined. The bentonite in its more purified form (i.e. free from any grit, sand, etc.) suitable for detergents contains at least 30% montmorillonite and thus its cation exchange capacity is at least about 50 to 75
25 meg per 100g of bentonite. Particularly preferred bentonites are the Wyoming or Western U.S. bentonites which have been sold as Thixo-jels 1, 2, 3 and 4 by Georgia Kaolin Co. These bentonites are known to soften textiles as described in British Patent No. 401,413 to Marriott and British Patent No. 461,221 to Marriott and Guam.

30

In addition, various other detergent additives or adjuvants may be present in the detergent product to give it additional desired properties, either of functional or aesthetic nature.

5 Improvements in the physical stability and anti-settling properties of the composition may be achieved by the addition of a small effective amount of an aluminum salt of a higher fatty acid, e.g., aluminum stearate, to the composition. The aluminum stearate stabilizing agent can be added in an amount of 0 to 3%, preferably 0.1 to 2.0% and more preferably 0.5 to 1.5%.

10

There also may be included in the formulation, minor amounts of soil suspending or anti-redeposition agents, e.g. polyvinyl alcohol, fatty amides, sodium carboxymethyl cellulose, hydroxy-propyl methyl cellulose. A preferred anti-redeposition agent is sodium carboxymethyl cellulose having a 2:1 ratio of
15 CM/MC which is sold under the tradename Relatin DM 4050.

Another minor ingredient is soil releasing agents, e.g. deflocculating polymers. In general, a deflocculating polymer comprises a hydrophilic backbone and one or more hydrophobic side chains.

20

The deflocculating polymer of the invention is described in greater detail in U.S. Pat. No. 5,147,576 to Montague et al. hereby incorporated by reference into the subject application,

25 The deflocculating polymer generally will comprise, when used, from about 0.1 to about 5% of the composition, preferably 0.1 to about 2% and most preferably, about 0.5 to about 1.5%.

Optical brighteners for cotton, polyamide and polyester fabrics can be used.

30 Suitable optical brighteners include Tinopal, stilbene, triazole and benzidine

sulfone compositions, especially sulfonated substituted triazinyl stilbene, sulfonated naphthotriazole stilbene, benzidine sulfone, etc., most preferred are stilbene and triazole combinations. A preferred brightener is Stilbene Brightener N4 which is a dimorpholine dianilino stilbene sulfonate.

5

Anti-foam agents, e.g. silicone compounds, such as Silicane L 7604, can also be added in small effective amounts.

Bactericides, e.g. tetrachlorosalicylanilide and hexachlorophene, fungicides,
10 dyes, pigments (water dispersible), preservatives, e.g. formalin, ultraviolet absorbers, anti-yellowing agents, such as sodium carboxymethyl cellulose, pH modifiers and pH buffers, color safe bleaches, perfume and dyes and bluing agents such as Iragon Blue L2D, Detergent Blue 472/372 and ultramarine blue can be used.

15

Also, soil release polymers and cationic softening agents may be used.

The list of optional ingredients above is not intended to be exhaustive and other optional ingredients which may not be listed, but are well known in the art, may
20 also be included in the composition.

Optionally, the inventive compositions may contain all or some the following ingredients: zwitterionic surfactants (e.g. Mirataine BET C-30 from Rhone-Poulenc Co.), cationic surfactants (e.g. Schercamox DML from Scher
25 Chemicals, Inc.), fluorescent dye, antiredeposition polymers, antidye transfer polymers, soil release polymers, protease enzymes, lipase enzymes, amylase enzymes, cellulase enzymes, peroxidase enzymes, enzyme stabilizers, perfume, opacifiers, UV absorbers, builders, and suspended particles of size range 300-5000 microns.

30

The compositions of the invention have a at least 50% transmittance of light using a 1 centimeter cuvette, at a wavelength of 410-800 nanometers, preferably 570-690 wherein the composition is substantially free of dyes.

5 Alternatively, transparency of the composition may be measured as having an absorbency in the visible light wavelength (about 410 to 800 nm) of less than 0.3 which is in turn equivalent to at least 50% transmittance using cuvette and wavelength noted above. For purposes of the invention, as long as one wavelength in the visible light range has greater than 50% transmittance, it is
10 considered to be transparent/translucent.

Enzyme deactivation as a result of UV-damage may occur at very low transmission of UV-B radiation.

15 **Bottle Material**

Clear bottle materials with which this invention may be used include, but are not limited to: polypropylene (PP), polyethylene (PE), polycarbonate (PC), polyamides (PA) and/or polyethylene terephthalate (PETE), polyvinylchloride (PVC); and polystyrene (PS).

20

The transparent or clear container according to the invention preferably has a transmittance of more than 25%, more preferably more than 30%, more preferably more than 40%, more preferably more than 50% in the visible part of the spectrum (approx. 410-800 nm).

Alternatively, absorbency of bottle may be measured as less than 0.6 or by having transmittance greater than 25% wherein % transmittance equals:

$$\frac{1}{10^{\text{absorbency}}} \times 100\%$$

5 For purposes of the invention, as long as one wavelength in the visible light range has greater than 25% transmittance, it is considered to be transparent/translucent.

10 Enzyme deactivation as a result of UV-damage may occur at very low transmission of UV-B radiation through the container wall.

The container of the present invention may be of any form or size suitable for storing and packaging liquids for household use. For example, the container
 15 may have any size but usually the container will have a maximal capacity of 0.05 to 15 L, preferably, 0.1 to 5 L, more preferably from 0.2 to 2.5 L. Preferably, the container is suitable for easy handling. For example the container may have handle or a part with such dimensions to allow easy lifting or carrying the container with one hand. The container preferably has a means suitable for
 20 pouring the liquid detergent composition and means for reclosing the container. The pouring means may be of any size of form but, preferably will be wide enough for convenient dosing the liquid detergent composition. The closing means may be of any form or size but usually will be screwed or clicked on the container to close the container. The closing means may be cap which can be
 25 detached from the container. Alternatively, the cap can still be attached to the container, whether the container is open or closed. The closing means may also be incorporated in the container.

The following examples are intended to further illustrate the invention and are
 30 not intended to limit the invention in any way:

All percentages, unless indicated otherwise, are intended to be percentages by weight.

- 5 All numerical ranges in this specification and claims are intended to be modified by the term about.

Finally, where the term comprising is used in the specification or claims, it is not intended to exclude any terms, steps or features not specifically recited.

10

Methodology

Measurement of Absorbency and Transmittance

- 15 Instrument: Milton Roy Spectronic 601

Procedure:

1. Both the spectrophotometer and the power box were turned on and
20 allowed to warm up for 30 minutes.
2. Set the wavelength.
 - type in the desired wavelength on the keypad (i.e., 590, 640, etc.)
 - press the [second function] key
 - 25 - press the "go to λ " [yes] key
 - machine is then ready to read at the chosen wavelength.
3. Zero the instrument.
 - press the [second function] key
 - 30 - press the "zero A" [% T/A/C]

- instrument should then read "XXX NM 0.000 A T"

4. Open the cover, place sample vertically and in front of the sensor.
- 5 5. Close the lid and record reading (ex. 640 NM 0.123 A T)

*Note: all readings are taken in "A" mode (absorbency mode)

*Note: zero instrument with every new wavelength change and/or new sample.

Absorbency Values for Two Typical Plastic Bottles		
Wavelength nm	Polyethylene (HDPE); 0.960 mm thickness	Polypropylene (PP); 0.423 mm thickness
254 (non-visible)	1.612	1.886
310 (non-visible)	1.201	0.919
360 (non-visible)	0.980	0.441
590 (visible)	0.525	0.190
640 (visible)	0.477	0.169

10

EXAMPLE 1

An aqueous solution of Acid Red 111 at 0.003% split into a 100 g and a 99.8 g portion. The 99.8 g sample had 0.2 g of Tinopal 5BM added to create a 0.2% solution. The samples were added to 5" diameter glass dishes with the top off and exposed to UV light of 254 nm and microwatt/cm² at 10" intensity for 72 hours. After each 24 hour period, the samples were weighed and topped off to 100 g to replace evaporated water. Absorption readings were taken with a UV/visible spectrum photometer at 530,550, and 570 nm initially and after irradiation at 254 nm. Results were as follows:

Sample	Initial Absorbance	72 Hour Absorbance	% Absorbance Loss
No f-dye – 530 nm	0.255	0.055	78.4
No f-dye – 550 nm	0.172	0.035	79.7
No f-dye – 570 nm	0.104	0.016	84.6
With f-dye – 530 nm	0.603	0.344	43.0
With f-dye – 550 nm	0.531	0.297	44.1
With f-dye – 570 nm	0.233	0.143	38.6

As can be seen in column 4, the loss in absorbance when f-dye is present is much less than in its absence indicating that the f-dye protects the colorant dye.

- 5 The absorbance readings in the presence of f-dye are generally higher than in their absence due to interaction of the f-dye with the colorant dye. To the eye, the sample with f-dye dramatically retains its original color when compared with the sample without f-dye which undergoes obvious color change – this visually confirms the spectrophotometric results.

CLAIMS

1. A transparent or translucent aqueous heavy duty liquid composition in a clear bottle comprising:
 - (a) 10 to 85% by wt. of a surfactant selected from the group consisting of anionic, nonionic, cationic, amphoteric, zwitterionic surfactants and mixtures thereof;
 - (b) 0.001 to 1% by wt. of a colorant dye; and
 - (c) 0.001 to 3% by wt. of a fluorescent dye and/or 0.001 to 3% by wt. of a UV absorber;wherein the composition has about 50% light transmittance or greater using 1 cm cuvette at wavelength of 410-800 nanometers; and
wherein the bottle has a light transmittance of greater than 25% at wavelength of about 410-800 nm.
2. A composition according to claim 1 characterised in that the UV absorber is selected from the group consisting of benzophenones, salicyclates, benzotriazoles, hindered amines and alkoxy and cinnamates.
3. A composition according to claims 1 or 2 characterised in that the fluorescent dye is selected from the group consisting of stilbeness; coumarin and carbostyryl compounds; 1,3-diphenyl-2-pyrazolines; naphthalimides; benzazdyl substitution products of ethylene, phenylethylene, stilbene, thiophene; and combined hateroaromatics.

4. A composition according to any preceding claim characterised in that the composition further comprises a protease.
5. A method of reducing destruction of colorant dye in a transparent or translucent liquid composition in a clear bottle which method comprises adding a UV absorber and/or a fluorescent dye to said composition.

INTERNATIONAL SEARCH REPORT

I. International Application No

PCT/EP 99/09374

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C11D3/42 C11D17/04 C11D3/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 131 826 A (COLGATE PALMOLIVE CO) 27 June 1984 (1984-06-27) claims 1-10, 16-18 example page 6, line 21 - page 7, line 7 ---	1-6
A	WO 94 11485 A (UNILEVER) 26 May 1994 (1994-05-26) claims 1-4, 10 examples page 11, line 15 - page 13, line 16 ---	1, 3-5
A	GB 2 172 608 A (COLGATE PALMOLIVE) 24 September 1986 (1986-09-24) claims 1, 7-9, 11-13 examples 1-3 page 2, line 20 - line 23 ---	1, 3-5
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

18 April 2000

Date of mailing of the international search report

04/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Neys, P

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 99/09374

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No
A	WO 98 53035 A (PROCTER & GAMBLE) 26 November 1998 (1998-11-26) abstract page 40, last paragraph -page 41, paragraph 1 page 46 ---	1,4
A	US 3 812 042 A (VERDIER D) 21 May 1974 (1974-05-21) cited in the application claims column 4, paragraph 64 - paragraph 75 ---	1,4
A	WO 97 26315 A (COLGATE PALMOLIVE CO) 24 July 1997 (1997-07-24) cited in the application claims 1,7 ---	1,4
P,A	EP 0 913 462 A (PROCTER & GAMBLE) 6 May 1999 (1999-05-06) claims 1,13,14 page 4, line 16 - line 57 ---	1,4
P,A	WO 99 36501 A (UNILEVER) 22 July 1999 (1999-07-22) examples ---	1,2,5
A	US 3 953 380 A (SUNDBY BJORN) 27 April 1976 (1976-04-27) abstract claims example 5 ---	1,3,5
A	US 3 954 675 A (INAMORATO JACK T ET AL) 4 May 1976 (1976-05-04) abstract claims examples ---	1,3,5
A	US 4 144 024 A (LALA ROBERT J) 13 March 1979 (1979-03-13) claim examples 1-3 -----	1,3,5

INTERNATIONAL SEARCH REPORT

Information on patent family members

I. National Application No

PCT/EP 99/09374

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2131826	A	27-06-1984	AT 395172 B	12-10-1992
			AT 433683 A	15-02-1992
			AU 558368 B	29-01-1987
			AU 2229183 A	21-06-1984
			BE 898436 A	13-06-1984
			BR 8306834 A	24-07-1984
			CA 1208578 A	29-07-1986
			CH 657146 A	15-08-1986
			DE 3344097 A	14-06-1984
			DK 572983 A,B,	14-06-1984
			ES 527960 D	01-10-1985
			ES 8600378 A	01-01-1986
			FI 834555 A,B,	14-06-1984
			FR 2537597 A	15-06-1984
			GR 79133 A	02-10-1984
			HK 71689 A	14-09-1989
			IT 1172373 B	18-06-1987
			MX 161813 A	28-12-1990
			NL 8304291 A	02-07-1984
			NO 834560 A,B,	14-06-1984
			NZ 206542 A	13-12-1985
			PH 20096 A	24-09-1986
			PT 77817 A,B	01-01-1984
			SE 460726 B	13-11-1989
			SE 8306839 A	14-06-1984
			SG 40189 G	17-11-1989
			ZA 8309050 A	31-07-1985
			ZM 8783 A	22-07-1985
			ZW 26883 A	28-03-1984
WO 9411485	A	26-05-1994	AU 5372494 A	08-06-1994
			EP 0670882 A	13-09-1995
GB 2172608	A	24-09-1986	US 4661287 A	28-04-1987
			AT 396369 B	25-08-1993
			AT 71486 A	15-12-1992
			AU 603334 B	15-11-1990
			AU 5469286 A	25-09-1986
			BE 904441 A	19-09-1986
			BR 8601198 A	25-11-1986
			CA 1294234 A	14-01-1992
			CH 678584 A,B	15-10-1991
			DE 3608558 A	25-09-1986
			DK 127486 A	20-09-1986
			EG 17692 A	30-08-1990
			ES 553115 D	01-05-1987
			ES 8705513 A	16-07-1987
			FI 861136 A	20-09-1986
			FR 2579221 A	26-09-1986
			GR 860724 A	21-07-1986
			HK 68992 A	18-09-1992
			IE 58877 B	01-12-1993
			IN 166183 A	24-03-1990
			IT 1191261 B	24-02-1988
			JP 7030356 B	05-04-1995
			JP 61218699 A	29-09-1986
			KR 9310381 B	23-10-1993
			LU 86360 A	06-10-1986

INTERNATIONAL SEARCH REPORT

Information on patent family members

National Application No

PCT/EP 99/09374

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2172608 A		NL 8600702 A	16-10-1986
		NO 861025 A,B,	22-09-1986
		NZ 215489 A	29-08-1989
		PH 24444 A	25-06-1990
		PT 82214 A,B	01-04-1986
		SE 8601227 A	20-09-1986
		SG 72492 G	02-10-1992
		TR 24373 A	20-09-1991
		US 4759876 A	26-07-1988
		ZA 8601812 A	28-10-1987
		ZM 2986 A	29-04-1988
		ZW 6286 A	10-12-1986
WO 9853035 A	26-11-1998	AU 7578198 A	11-12-1998
US 3812042 A	21-05-1974	FR 2136913 A	29-12-1972
		AU 4408872 A	03-01-1974
		DE 2231304 A	18-01-1973
		GB 1382295 A	29-01-1975
		JP 48061508 A	29-08-1973
		PH 9542 A	09-01-1976
WO 9726315 A	24-07-1997	AU 1535897 A	11-08-1997
EP 0913462 A	06-05-1999	AU 1376899 A	24-05-1999
		WO 9923196 A	14-05-1999
WO 9936501 A	22-07-1999	AU 2279899 A	02-08-1999
US 3953380 A	27-04-1976	AU 470119 B	04-03-1976
		AU 3353071 A	22-03-1973
		BE 774464 A	14-02-1972
		CA 951212 A	16-07-1974
		CH 571055 A	31-12-1975
		DE 2152141 A	04-05-1972
		DK 140262 B	16-07-1979
		ES 394975 A	01-12-1974
		FR 2111248 A	02-06-1972
		GB 1366905 A	18-09-1974
		IT 942199 B	20-03-1973
		NL 7114896 A,C	03-05-1972
		PH 11172 A	28-10-1977
		SE 392730 B	18-04-1977
		ZA 7105801 A	25-04-1973
US 3954675 A	04-05-1976	AU 5550473 A	14-11-1974
		CA 995863 A	31-08-1976
		DE 2326467 A	13-12-1973
		FR 2186531 A	11-01-1974
		GB 1432462 A	14-04-1976
		DK 146657 B	28-11-1983
		IT 985277 B	30-11-1974
US 4144024 A	13-03-1979	NONE	

